



[www.cemanco.com](http://www.cemanco.com)

951 NW 31st Avenue, Pompano Beach, FL 33069

Phone: 954-970-3099 - Fax: 954-970-3056

E-Mail: [sales@cemanco.com](mailto:sales@cemanco.com)



## HT-TC026Y MANUAL HYDRAULIC CUTTING TOOL

Hand operated hydraulic tool specifically designed to cut Copper, Aldrey, Aluminum, Aluminum-Steel cables, steel ropes having a max overall diameter of 1", guy wire up to **7/8"** and steel ground rod up to **5/8"**.

The tool features a double speed action. The blades are manufactured from high strength special steel, heat treated to ensure a long service life.

The head can rotate by **180 degrees**, to enable the operator to work in the most comfortable position, and can easily be opened to allow the cutting of running cables. The **HT-TC026Y** features an automatic safety valve to bypass oil when reaching maximum pressure; a pressure release device can also be operated at any stage of operation.



# CEMANCO

www.cemanco.com

951 NW 31st Avenue, Pompano Beach, FL 33069

Phone: 954-970-3099 - Fax: 954-970-3056

E-Mail: sales@cemanco.com

## HT-TC026Y

CUTTING CAPACITY			
MATERIAL	TENSILE STRENGTH (lbs./sq.in.)	MAX CUTTING DIAMETER (in)	
		HT-TC026Y TC 025 B-TC026YA	
ROPE & CONDUCTORS	COPPER	≤ 59,450	1
	ALUMINUM	≤ 29,000	1
	ALMELEC	≤ 49,300	1
	STEEL	≤ 261,000	FEW INDICATIVE EXAMPLES: 7 x 0.118 = Ø out. 0.354 19 x 0.083 = Ø out. 0.413 19 x 0.091 = Ø out. 0.453
	MULTI STRANDS STEEL (STRANDS Q. TY ≥ 200)	≤ 264,000	0.709
	ACSR	≤ 261,000	1  FEW INDICATIVE EXAMPLES: 26 x 0.098 + 7 x 0.077 : Ø out. = 0.624 26 x 0.120 + 7 x 0.094 : Ø out. = 0.763 26 x 0.142 + 7 x 0.110 : Ø out. = 0.897
RODS	STEEL	≤ 87,000	0.511
		≤ 60,900	0.629
	COPPER	≤ 43,000	0.787
		≤ 36,250	0.905
	ALUMINUM	≤ 23,200	1

Max cutting Ø in.	Dimensions in.		Weight lbs
	length	width	
up to 1	15.5	5.1	7.7

STORAGE				
Type	Dimensions in	Weight lbs	Supplied with the tool	Available upon request
Canvas bag 001	16.9x6.1	0.33	✳	—

**Ideal for EHS guy wire up to 7/8”  
and ground rod up to 5/8”**